



US versus UK approach for TV Whitespace: A quick comparison

Georg Schöne, Chief Technical Officer, LS telcom AG

WSRD Workshop, 31.03.2014

Overview




- There are currently several tests going on around the globe
- Two very different approaches are the US and the UK one
- The technical requirements have strong impact on a potential business model
- US model is ok in rural areas but insufficient in major cities.
- Examples are shown on the next slides

WSDB Challenge: Channels Availability



Example: Sweet Grass, Canadian Boarder



Infrastructure Site

(4W but reserved channels)

2	✓	3	✗	4	✗	5	✓	6	✓	7	✓	8	✓	9	✓	10	✓	11	✓
12	✓	13	✓	14	✓	15	✓	16	✓	17	✓	18	✓	19	✓	20	✓	21	✓
22	✓	23	✓	24	✓	25	✓	26	✗	27	✗	28	✗	29	✓	30	✓	31	✓
32	✓	33	✓	34	✓	35	✓	36	✗	37	✗	38	✗	39	✓	40	✓	41	✓
42	✓	43	✓	44	✓	45	✓	46	✓	47	✓	48	✓	49	✓	50	✓	51	✗

-> 41 channels available

Low Power Site

(100mW, no reserved channels)



2	✗	3	✗	4	✗	5	✗	6	✗	7	✗	8	✗	9	✗	10	✗	11	✗
12	✗	13	✗	14	✗	15	✗	16	✓	17	✓	18	✓	19	✗	20	✗	21	✓
22	✓	23	✓	24	✓	25	✓	26	✗	27	✗	28	✗	29	✓	30	✓	31	✓
32	✓	33	✓	34	✓	35	✓	36	✗	37	✗	38	✗	39	✓	40	✓	41	✓
42	✓	43	✓	44	✓	45	✓	46	✓	47	✓	48	✓	49	✓	50	✓	51	✗

-> 25 channels available

WSDB Challenge: Channels Availability



Example: Annapolis/Maryland



Infrastructure Site
(4W but reserved channels)

2	✓	3	✗	4	✗	5	✓	6	✗	7	✗	8	✗	9	✗	10	✗	11	✗
12	✗	13	✗	14	✗	15	✗	16	✗	17	✗	18	✗	19	✗	20	✓	21	✓
22	✓	23	✓	24	✗	25	✗	26	✗	27	✗	28	✗	29	✗	30	✗	31	✗
32	✗	33	✗	34	✗	35	✗	36	✗	37	✗	38	✗	39	✗	40	✗	41	✗
42	✗	43	✗	44	✗	45	✗	46	✗	47	✗	48	✗	49	✗	50	✗	51	✗

-> 6 channels available

Low Power Site
(100mW, no reserved channels)


2	✗	3	✗	4	✗	5	✗	6	✗	7	✗	8	✗	9	✗	10	✗	11	✗
12	✗	13	✗	14	✗	15	✗	16	✗	17	✗	18	✗	19	✗	20	✗	21	✓
22	✓	23	✓	24	✗	25	✗	26	✗	27	✗	28	✗	29	✗	30	✗	31	✗
32	✗	33	✗	34	✗	35	✗	36	✗	37	✗	38	✗	39	✗	40	✗	41	✗
42	✗	43	✗	44	✗	45	✗	46	✗	47	✗	48	✗	49	✗	50	✗	51	✗

-> 3 channels available

WSDB Challenge: Channels Availability



Example: Washington, DC



Infrastructure Site

(4W but reserved channels)

2	✓	3	✗	4	✗	5	✗	6	✗	7	✗	8	✗	9	✗	10	✗	11	✗
12	✗	13	✗	14	✗	15	✗	16	✗	17	✗	18	✗	19	✗	20	✓	21	✓
22	✗	23	✗	24	✗	25	✗	26	✗	27	✗	28	✗	29	✗	30	✗	31	✗
32	✗	33	✗	34	✗	35	✗	36	✗	37	✗	38	✗	39	✗	40	✗	41	✗
42	✗	43	✗	44	✗	45	✗	46	✗	47	✗	48	✗	49	✗	50	✗	51	✗

-> 3 channels available

Low Power Site

(100mW, no reserved channels)

2	✗	3	✗	4	✗	5	✗	6	✗	7	✗	8	✗	9	✗	10	✗	11	✗
12	✗	13	✗	14	✗	15	✗	16	✗	17	✗	18	✗	19	✗	20	✗	21	✓
22	✗	23	✗	24	✗	25	✗	26	✗	27	✗	28	✗	29	✗	30	✗	31	✗
32	✗	33	✗	34	✗	35	✗	36	✗	37	✗	38	✗	39	✗	40	✗	41	✗
42	✗	43	✗	44	✗	45	✗	46	✗	47	✗	48	✗	49	✗	50	✗	51	✗

-> 1 channels available


US vs. UK model: External communication



Dynamic Spectrum DB	National Frequency register	Neighbour countrys frequency DB's	Other Dyn. Spectr. DB'S (if any)	Devices and Sensors
	<p>US: DB's download TX data</p> <p>UK: Ofcom delivers preprocessed Info</p> <p>US: DB's download TX data</p> <p>UK: Ofcom delivers preprocessed Info</p> <p>Update of national licensing information</p>	<p>US: DB's contact Neighbours</p> <p>UK: Ofcom delivers preprocessed Info</p> <p>Update of international licensing information</p>	<p>US: Registration of PMSE time by DB's</p> <p>UK: Registration of PMSE via Regulator</p>	<p>Sensor information about local Interference</p>

US vs. UK model: Device communication



Component	Step1	Step2	Step3	Step4	Step5	Step6	Step7
Device or network element	 Secure connection is initiated		Report position and device information	UK: Probability analysis Analyse inter-fERENCE		 Check for best quality	 Negotiate with neighbours
Spectrum DB							

US vs. UK model: Differences




- The UK model ties the database operators much closer to the Regulator
- The matrixes containing the key information about coverage probability for DTT and PMSE are delivered by Ofcom
- The applied UK propagation model is more sophisticated, considering terrain effects
- Pixel based approach: coverage is distinguished in bins of 50x50m
- Update frequency in US: 15 minutes in UK: 3 hours
- Probability approach: a certain influence on DTT is accepted as long as the residual coverage probability is high enough

Short summary



- Both models have their pro's and con's
- The US approach will not work too perfect in central Europe's high popualtion density
- The complex UK approach may raise substantial computation power requirements at the regulator if faster turn around times are required.



Thank you for your attention!



Im Gewerbegebiet 31-33
D-77839 Lichtenau
GERMANY
gschoene@LStelcom.com
Tel. +49 (0)7227 9535 600
www.LStelcom.com

Disclaimer



Copyright (c) 2013 by LS telcom AG

This document must neither be copied wholly or partly, nor published or re-sold without prior written permission of LS telcom. The information contained in this document is proprietary to LS telcom. The information shall only serve for documentation purposes or as support for education and training purposes and for the operation and maintenance of LS telcom products. It must be treated strictly confidential and must neither be disclosed to any third party nor be used for other purposes, e.g. software development, without the written consent of LS telcom.

This document may contain product names, e. g. MS Windows, MS Word, MS Excel and MS Access, which are protected by copyright or registered trademarks / brand names in favour of their respective owners.

LS telcom make no warranty or representation relating to this document and the information contained herein. LS telcom are not responsible for any costs incurred as a result of the use of this document and the information contained herein, including but not limited to, lost profits or revenue, loss of data, costs of recreating data, the cost of any substitute equipment or program, or claims by any third party.

Urheberrecht der LS telcom AG

Dieses Dokument darf ohne ausdrückliche Zustimmung der LS telcom AG weder insgesamt noch teilweise kopiert, veröffentlicht oder weitergegeben werden. Die Information in diesem Dokument ist intellektuelles Eigentum von LS telcom. Die Information ist nur für Dokumentationszwecke oder die Nutzung für Ausbildung und Training bestimmt, sowie für die Nutzung und Wartung von LS telcom Produkten. Die Information ist streng vertraulich zu behandeln und darf ohne ausdrückliche Zustimmung der LS telcom AG weder Dritten Parteien offenbart, noch für andere Zwecke genutzt werden, beispielsweise für Softwareentwicklung.

Dieses Dokument kann Produkt- und Markennamen enthalten, beispielsweise MS Windows, MS Word, MS Excel und MS Access, die durch Urheberrecht, Markenrecht oder Namensrecht der jeweiligen Rechteinhaber geschützt sind.

LS telcom gibt keinerlei Garantie oder Zusicherung im Zusammenhang und aus diesem Dokument und der darin enthaltenen Information. LS telcom übernimmt keinerlei Haftung für Schäden, Kosten und Aufwendungen, die aus der Nutzung dieses Dokuments und der darin enthaltenen Information entstehen, inklusive, aber nicht nur, für entgangener Gewinne oder Umsätze, Datenverlust, Kosten der Datenwiederherstellung, Aufwendungen für die Ersatzbeschaffung von Hardware oder Software, oder für Ansprüche dritter Parteien.